Infrared Camera Selection Guide





















	PTi120	TiS20+/ Ti20+ MAX	TiS60+	TiS55+	TiS75+	Ti300+	Ti401 PRO	Ti480 PRO	TiX501	TiX580
Key Features										
Infrared Resolution	120 × 90 120 × 90 (10,800 pixels) (10,800 pixels)		320 × 240 (76,800 pixels)	256 × 192 384 × 288 (49,152 pixels) (110,592 pixels)		320 × 240 (76,800 pixels)	640 × 480 (307,200 pixels)		640 × 480 (307,200 pixels)	
SuperResolution				-				Yes, in software.	-	Yes, in software.
Temperature Range	-20°C to 400°C (150°C for TiS20+)		-20°C to 400°C	-20°C to 550°C		-20°C to 650°C		-20°C to 1,000°C	−20°C to 650°C	-20°C to 1,000°C
IFOV with Standard Lens (spatial resolution)	7.6 mRad, D:S 130:1		1.86 mRad, D:S 532:1	1.91 mRad		1.85 mRad, D:S 532:1	0.93 mRad, D:S 1065:1		0.93 mRad, D:S 1065:1	
Field of View	50°H × 38°V		34.1°H × 25.6°V	28°H × 20°V	42°H × 30°V		34°H × 24°V		34°H × 24°V	
Minimum Focus Distance	22.8 cm 50 cm 46 cm			50 cm		15 cm			n	
MultiSharp Focus	Yes, focused throughout the field of view							Yes, focused throughout the field of view		
LaserSharp Auto Focus	Fixed Focus			Manua	l Focus	Yes, for consistently in-focus images. Every. Single. Time				
Laser Distance Meter	-					Yes, calculates distance to the target for precisely focused images and displays distance on screen				
Advanced Manual Focus	Fixed Focus			Manual Focus		Yes				
Wireless Connectivity	Yes, to PC, iPhone® and iPad® (iOS 4s and later), Android™ 4.3 and up, and WiFi to LAN (where available)									
Fluke Connect® App Compatible	Yes*, connect your camera to your smartphone, and images taken automatically upload to the Fluke Connect® app for saving and sharing									
IR-Fusion Technology	AutoBlend continuous 0% to 100%. Adds the context of the visible details to your infrared image									
Battery Life	≥ 2 hours continuous (without WiFi)	≥ 5 hours continuous (without WiFi)	4 hours continuous use per battery pack		2-3 hours continuous (without Wifi) 2-3 hours continuous use per per battery pack 2-3 hours continuous use per battery pack 2-3 hours continuous use per battery 2-3 hours continuous use per battery				use per battery pack	
Warranty	Two years (standard)									